

Safety Data Sheet dated 21/1/2016, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: 9.BFKERAMIK/8 - 9.BFKERAMIK250/6

Trade code: KERAMIK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Abrasive compound for bodywork

Professional use only Uses advised against:

All not indicated in the suggested uses.

1.3. Details of the supplier of the safety data sheet

Company:

RUPES SPA - Via Marconi 3A, 20080, Vermezzo (MI) - Italy

RUPES SPA - Telefono n°+3902946941

Competent person responsible for the safety data sheet:

info_rupes@rupes.it

1.4. Emergency telephone number

For United States, Canada Puerto Rico and Virgin Island: 1-800-255-3924

For China: 400-120-0751 For Brazil: 0-800-591-6042 For India: 000-800-100-4086 For Mexico: 01-800-099-0731

For Europe and all the other countries: 001-813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

P102 Keep out of reach of children.

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

KERAMIK/1

Page n. 1 of 9



None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification	
>= 7% - < 10%	Hydrocarbons, C11 C14, n-aklkanes, isoalkanes, zycloalkanes, <2% aromatics	EC: 926-141-6 REACH No.: 01-21194566 20-43	3.10/1 Asp. Tox. 1 H304 EUH066	
>= 3% - < 5%	White mineral oil (petroleum)	CAS: 8042-47-5 EC: 232-455-8 REACH No.: 01-21194870 78-27	3.10/1 Asp. Tox. 1 H304	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

4.2. Most important symptoms and effects, both acute and delayed

None

4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

KERAMIK/1

Page n. 2 of 9



Suitable extinguishing media:

Water.

Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

KERAMIK/1



Adequately ventilated premises.

7.3. Specific end use(s)

Abrasive compound for bodywork

Professional use only

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

9.BFKERAMIK/8 - 9.BFKERAMIK250/6

- OEL Type: TLV-TWA - LTE(8h): 4 mg/m3

- OEL Type: TLV-TWA - LTE(8h): 10 mg/m3

DNEL Exposure Limit Values

N.A.

PNEC Exposure Limit Values

N.A.

8.2. Exposure controls

Eye protection:

Wear eye/face protection

Protection for skin:

Wear suitable protective clothing

Protection for hands:

When handling with chemical substances, protective gloves must be worn with the CE-Label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances

Respiratory protection:

In case of inadequate ventilation wear respiratory protection

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	light grey paste		
Odour:	characteristic		
Odour threshold:	N.A.		
pH:	N.A.		
Melting point / freezing point:	N.A.		



Initial boiling point and	N.A.	
boiling range:		
Flash point:	> 70 ° C	
Evaporation rate:	N.A.	
Solid/gas flammability:	N.A.	
Upper/lower flammability	N.A.	
or explosive limits:		
Vapour pressure:	N.A.	
Vapour density:	N.A.	
Relative density:	1 g/cm3	
Solubility in water:	easily suluble	
Solubility in oil:	N.A.	
Partition coefficient	N.A.	
(n-octanol/water):		
Auto-ignition temperature:	N.A.	
Decomposition	N.A.	
temperature:		
Viscosity:	16000-19000	 dynamic viscosity at 20°C
	mPa-s	
Explosive properties:	N.A.	
Oxidizing properties:	N.A.	

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.		
Fat Solubility:	N.A.		
Conductivity:	N.A.		
Substance Groups relevant properties	14.00%		solvent content

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures

10.5. Incompatible materials

None in particular.

10.6. Hazardous decomposition products

KERAMIK/1

Page n. 5 of 9



None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

Hydrocarbons, C11 C14, n-aklkanes, isoalkanes, zycloalkanes, <2% aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 5000 mg/kg - Source: OECD-Richtlinien 401 Test: LD50 - Route: Skin - Species: Rabbit = 5000 mg/kg - Source: OECD-Richtlinien 402

White mineral oil (petroleum) - CAS: 8042-47-5

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg - Source: OECD 402
Test: LD50 - Route: Inhalation - Species: Rat > 5000 mg/l - Duration: 4h - Source: OECD 403

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity:
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

White mineral oil (petroleum) - CAS: 8042-47-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96

12.2. Persistence and degradability

N.A

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

KERAMIK/1



12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) 2015/830

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

No restriction.

Restrictions related to the substances contained:

KERAMIK/1



No restriction.

Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

NΑ

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of phrases referred to in Section 3:

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of

Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

KERAMIK/1

Page n. 8 of 9



IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LTE: Long-term exposure.

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STE: Short-term exposure.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.

(ACGIH Standard).

WGK: German Water Hazard Class.